

ANTI-STATIC DRY CEMENT DELIVERY

300 PSI / 20 BAR

MADE IN ITALY

TECHNOFLEX - ITALY ANTI-STATIC DRY CEMENT DELIVERY HOSE W. P. 300 PSI/20 BAR



TechnoFlex Dry Cement Delivery Hose - 300 PSI / 20 BAR

Constructed with a highly durable tube and cover, utilizing top-grade elastomer compounds to ensure exceptional abrasion resistance and long-lasting performance. Engineered for the efficient transfer of dry materials and slurries, making it an ideal choice for handling dry cement, pebble, lime brine, barite, and other highly abrasive media in demanding industrial applications.

- **Temperature Range:**

- -30°C to +80°C

- **Reinforcement:**

- Multiple textile plies.

- **Tube:**

- Black NR/SBR rubber blend.

- **Cover:**

- Black NR/SBR rubber blend.

- **Standard Length:**

- 20m /60m

- **Safety Factor:**

- 4:1

HOSE I.D.		Reinf. Plies	HOSE O.D.		Bend Radius		WORKING PRESSURE		BURST PRESSURE		WEIGHT
in	mm		in	mm	in	mm	psi	bar	psi	bar	Kg/m
2	50.8	2	2.882	73.2	12	300	300	20	1,200	80	2.24
2 1/2	63.5	2	3.382	85.9	15	375	300	20	1,200	80	2.65
3	76.2	2	3.921	99.6	20	500	300	20	1,200	80	3.36
4	101.6	2	4.953	125.8	28	700	300	20	1,200	80	4.40
5	127.0	2	6.079	154.4	25	625	300	20	1,200	80	5.56
6	152.4	2	7.087	180.0	36	900	150	10	600	40	6.60
8	203.2	2	9.362	237.8	56	1,400	150	10	600	40	10.97
10	254.0	2	11.512	292.4	80	2,000	150	10	600	40	14.89
12	304.8	2	13.591	345.2	110	2,750	150	10	600	40	18.50

Authorized Distributor:
GEOMAC INTERNATIONAL TRADING & CONTRACTING WLL



Dewatering Pump Sales | Dewatering Accessories | Hoses & Fittings | Pump Parts | Pump Rental | Pump Service

✉ E-mail: sales@geo-mac.com

www.geo-mac.com

📍 Shop No. 0, Building 270, Road / Street 336

Block 312, MANAMA / ALGUFUL

Kingdom of Bahrain

📞 Phone Number: +973 17769636