



Aqualiner US MSHA Accepted Heavy Duty Layflat Hose

Purpose

High pressure sprinkling & dewatering, Light gravel or mud discharge, Construction, industrial, agriculture & marine service industries.



Application

- Underground mining
- High pressure sprinkling & dewatering
- Light gravel or mud discharge
- Construction, mining, industrial, agriculture & marine service industries

Features

- Flame resistant (US MSHA IC-257/2)
- Excellent performance on sloped ground
- 6~10.5kgf/cm² working pressure
- Abrasion resistant
- Constructed with high grade strength polyester yarn reinforcement
- Lightweight and compact for economical storage
- 100 meter continuous coiled

Nomal Size		I.D.		O.D.		Standard Length		W.P(at20°C)	
mm	inch	mm	inch	mm	inch	m	ft	kg/cm2	PSI
040	1.5	41.0	1.614	1.9	0.075	100	328	10	150
050	2	53.1	2.090	2.0	0.079	100	328	10	150
065	2 ½	65.5	2.578	2.1	0.083	100	328	10	150
075	3	78.5	3.090	2.3	0.090	100	328	10	150
100	4	105.0	4.134	2.5	0.098	100	328	10	150
150	6	157.0	6.181	2.7	0.106	100	328	8	116
200	8	207.0	8.149	3.0	0.118	100	328	8	116