

Alfaflex Wire Reinforced Steam Hose 250 PSI

All steam and hot water/steam applications where superior life, safety and performance are important. Special EPDM cover provides substantially longer service life due to its heat age resistance.



- T** Black EPDM compound
- C** Red EPDM compound
- R** Multiple steel wire cord plies
- T.P.** -40°F to +450° F (-40°C to + 230°C)
- S.F.** 10:1
- B** ALFAFLEX Steam Hose 250 - PSI W.P.

* T - Tube, C - Cover, R - Reinforcement, T.P. - Temperature, S.F. - Safety Factor, B - Branding.

I.D.		O.D.		Standard Length		Working Pressure		Approx. Weight
in	mm	in	mm	ft	m	PSI	kg/cm ²	kg/m

1/2	12.7	0.972	24.7	200	60	250	17	0.71
3/4	19.1	1.222	31.1	200	60	250	17	0.88
1	25.4	1.472	37.4	200	60	250	17	1.06
1 1/2	38.1	2.130	54.1	200	60	250	17	1.92
2	50.8	2.661	67.6	200	60	250	17	2.66
2 1/2	63.5	3.350	85.1	200	60	250	17	4.42
3	76.2	3.850	97.8	200	60	250	17	5.57

* Standard Hose Length : 200ft(60m), 100ft(30m)